

**DAWN ENTERPRISES INC.**

9155 Sweet Valley Dr., Valley View, OH 44125  
Phone: (216) 447-1777 or (800) 548-4867  
Fax: (216) 447-3416  
www.Dawn-Ent.com

**INSTALLATION INSTRUCTIONS**

PART NUMBER: CIV16-4DR-PED  
FOR: 2016+ HONDA CIVIC 4 DR  
EFFECTIVE: 3/26/17

**INSTALLATION PACKAGE INCLUDES:**

- A) 4 – 3/4" Mounting Screws
- B) 4 – Lock Washers
- C) 4 – Flat Washers
- D) 2 – Red Electrical Connectors
- E) 1 – 3/8" Harness
- F) 5 – Paper Hole Locators

**EXTRA TOOLS NEEDED:** Masking Tape, Tape Measurer, Electrical Tape, Drill, 1/8" Drill Bit, Uni-Bit

**PLEASE READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION**

1. Remove trunk liner.
2. Place the Sportwing® onto the deck lid and measure 7 3/4" from the tip on the trunk to the tip of the Sportwing® on both the driver and passenger sides. Then, measure 5" from the tip of the Sportwing® to the edge of the trunk on both sides (As shown in diagrams A and B below).

(DIAGRAM A)



(DIAGRAM B)



3. Next, take a grease pencil and outline the pedestal feet of the Sportwing® on both the driver and passenger sides. Place the Sportwing® aside on a soft cloth to prevent scratching. Proceed to place a cover or blanket inside of the trunk to protect it from metal shavings from drilling. Place the 5 Hole Locators (provided) precisely over the 4 thread holes and the 1 harness hole on the bottom of the pedestal feet (As shown in diagram C below).

(DIAGRAM C)



4. Carefully flip the Sportwing® upside-down on a soft surface, leaving the Hole Locators still fastened to the mounting holes and harness hole. Make sure that the Hole Locators have not moved off the holes. Place the Sportwing® back onto the outline marks that you made in the previous step. Next, after Sportwing® is aligned, tape the hole locators onto the deck lid using masking tape. After all 5 holes are fastened, carefully lift the Sportwing® up from the deck lid, leaving the Hole Locators taped onto the deck lid. Set the Sportwing® aside on a soft surface.
5. Using a 1/8" or similar drill bit, drill a 1/8" pilot hole in the exact center of each of the 5 hole locations. After drilling, remove the Hole Locators. Next, using a uni-bit, open the 5 pilot holes to 7/16".
6. Apply Zinc Chromate primer or touch-up paint on the edges of the 5, 7/16" holes that you drilled to prevent rusting.
7. Close the trunk, remove the paper liner from the bottom of the mounting area and feed the harness wires of the Sportwing® through the 7/16" harness hole (NOTE: make sure that you do not crimp the brake light wires when you place the Sportwing® back onto the outline marks). When satisfied with the alignment (and that all the holes are the correct size), firmly press the Sportwing® into place.
8. Using provided Mounting Screws with lock washers and flat washers, install screws into the 4 mounting holes and partially tighten all 4 mounting screws. After all 4 are slightly tightened, tighten all evenly until they are tight. DO NOT OVER-TIGHTEN.
9. Run the Sportwing® wires towards the driver side trunk hinge. Insert the brake light wires into the provided harness, and using black electrical tape, fasten the wire to allow the trunk to open and close. Next, run the wires toward the third brake light. Using the provided Electrical Connectors, connect the white (hot) wire of the Sportwing® to the green wire of the brake light. Then, connect the white wire with the blue stripe (ground) wire of the Sportwing® to the black wire of the third brake light. Step on the brake pedal to test the connections.
10. Clean up any metal shavings, and you are done. If you have any questions, or would like more information about other quality Sportwing® products, please call the TOLL-FREE number at the top of this sheet. Thank you for choosing Dawn Enterprises Inc.